BERTIN

Bertin 6150 AD 6

Handheld survey meter

Handheld survey meter with an energy-compensated GM counter for ambient dose equivalent H*(10), waterproof to IP67. The AD 6 version is designed for low dose rates from 0.01 µSv/h.



Detector type	Energy range	Weight
Energy-compensated GM, H*(10) [1]	**60 keV–1.3 MeV** [1]	**400 g** [1]

Specifications

DETECTOR		
Detector type	Energy-compensated GM, H*(10)	[1]
MEASURING RANGE		
Energy range	60 keV–1.3 MeV	[1]
CONNECTIVITY & INTERFACE		
Dose-rate display range	0.01 µSv/h–10 mSv/h	[1]
Dose display range	1 µSv–100 mSv	[1]
Communication	RS232	[1]
POWER & BATTERY		
Power supply	9 V battery	[1]
MECHANICAL		
Dimensions	130 × 80 × 29 mm	[1]
Weight	400 g	[1]
ENVIRONMENT & RATINGS		
perating temperature	–30 to +50 °C	[1]
Operating time	1000 hours	[1]
IP rating	IP67	[1]

Sources

[1] **Survey meter 6150 AD 5 and 6**
Bertin Technologies · product-page · product page · checked 2026-10-16
https://www.bertin-technologies.com/product/survey-meters/survey-meter-6150-ad-5-and-6/

Every value is taken from the manufacturer’s own document; the number after the value refers to the source list. Always check against the latest datasheet before ordering.

The data comes from the manufacturer’s published documents. Manufacturers may change specifications; the current configuration and performance are confirmed in the quotation.